

WESTMINSTER FIXED HVM BOLLARD

Operation Types: Fixed Security Bollard



PRODUCT OVERVIEW

The ATG Access Westminster, Fixed High Security Bollard is manufactured from micro-engineered steel which has a high impact 'toughness' and the ability to absorb massive amounts of energy without fracturing. This material is incredibly strong and corrosion resistant.

This heritage style bollard is available in a lift-out, shallow foundation or traditional depth fixed model.

With a ribbed profile and peaked top, within the front facia there is a specifically designed section to enable a corporate logo or crest to be inserted. The product can be supplied unpainted or with a primed finish. Typically finished in black paint.

Installed within a foundation depth of 750 mm, the Westminster fixed bollard is ideal for applications where foundation depth is not an issue and where no restrictions apply.

The foundation for this product is a concrete and rebar structure with 1.2 spacings needing to be adhered to in order to comply with PAS 69.

You will find the City of Westminster crest displayed on most of the bollards installed within the Westminster area. You will find these incredibly strong products as far afield as Melbourne, Australia!

SECURITY RATING

Traditional Depth Static:
PAS 68: V/ 7500[N3]/64/90:0.0/5.3

FINISHES

Manganese steel, supplied raw (unpainted) as standard with a blank front facia. Can be primed, painted and fitted with a corporate logo or crest.

WESTMINSTER FIXED BOLLARD	
	Fixed
Bollard Diameter	273 mm (front face) 133 mm (side profile)
Height Above Ground	1,065 mm
Foundation Depth	750 mm
Finishes Available	Black Manganese Steel Unpainted. Can be primed on request and fitted with a logo or crest.
Security Rating	PAS 68: V/7500[N3]/64/90:0.0/5.3

