CITYSCAPE GATE

Operation Type: Manually Operated, Shallow Foundation Gate





PRODUCT OVERVIEW

The Cityscape Gate is an impact tested swing gate. This strong frangible gate requires just 300 mm of foundation depth for installation.

Ideal for protecting entrances from 4 to 6 meters wide, the gate is manually opened and closed and may be secured in the closed position by an automated or manual locking mechanism, the gate may be secured from a remote location electronically if required. Able to be opened from both inwards and outwards, this provides flexible, secured access for vehicles.

A 4.5 m version of this innovate structure is impact tested and successfully arrested a 7,500 kg truck travelling at 64 kph (40 mph).

Available in brushed stainless steel or a coated finish, this product can span 4 m to 6 m in width. This product can be specified as a right or left hand hinged gate and can be opened in either direction depending on site requirements.

This aesthetically pleasing high security product is ideal for access points with minimal operations each hour and is a cost effective way of preventing access to unauthorised vehicles and pedestrians.

The gate can also be used within a tiger-trap security design if required so that vehicles can be searched before entry for ultra-secure sites.

SECURITY RATING

Meets the BSI PAS 68 rating, tested variant was 4.5 m wide:

V/7.500(N2)/64/90:1.09/2.40

FINISHES

Available in brushed stainless steel or coated to any RAL colour specified.
Reflective tape can also be used to increase visibility if required.

CITYSCAPE GATE STATISTICS	
	Manually Operated
Widths Available	4,000 mm – 6,000 mm. End posts have a diameter of 355 mm
Height Above Ground	920 mm – bar height
Foundation Depth	From 300 mm
Finishes Available	Brushed stainless steel as standard. Also available with a RAL coloured coating if required and reflective tape.
Security Rating	PAS 68: V/7,500(N2)64/90:1.09/2.40



BBC Headquarters, Undisclosed