

TITAN MK II HIGH SECURITY BOLLARD

Operation Type: Manually Retractable



PRODUCT OVERVIEW

The Titan MK II is an impact tested bollard and is available in a variety of operating sets and arrays. Tested to withstand a 7,500 kg vehicle travelling at 80 kph, this product is suitable to protect against high velocity attacks.

The Titan MK II bollard is a strong, economical and effective way of protecting your key access points.

The product can be operated as standard with a hydraulic pump system or as a manually operable, standalone unit.

All steel parts are hot dip galvanised or sherardized for corrosion protection. This also ensures long term reliability of the product.

MANUALLY RETRACTABLE

Available as a manually operable variant; the product is operated through the simple use of a hand-held battery drill or a manual hand crank.

No electricity or hydraulics are required to raise or lower the bollard and the product can be operated with ease (can be raised or lowered in 12 seconds).

This product is ideal for remote sites with little or limited access to an electricity supply or gateways used very infrequently.

ATG estimates the total saving for a manual system to be up to 50% of the automatic system.

SECURITY RATING

Impact Test Certification:

PAS 68: V/7,500/80/90:4.0/33.5

FINISHES

Galvanised and painted, black sherardized or fitted with an aesthetic sleeve; this product has as a stainless-steel top lid and two machine bands as standard.

TITAN MK II MANUALLY RETRACTABLE BOLLARD

Manually Retractable

Bollard Diameter	273 mm
Height Above Ground	1,000 mm
Foundation Depth	1,684 mm
Finishes Available	Supplied either galvanised and painted or sherardized black as standard with two yellow reflective bands. Can be fitted with an aesthetic sleeve if required. Supplied with a stainless-steel top lid & two machine bands.
Security Rating	PAS 68: V/7,500/80/90:4.0/33.5

