

SP40 HIGH-SECURITY FIXED BOLLARD



Technical Specifications

Bollard Diameter	219 mm
	254 mm if fitted with an aesthetic sleeve
Height Above Ground	1,000 mm
Foundation Depth	600 mm
Finishes Available	Galvanised as standard with banding optional. Can be powder coated to a specified RAL finish or fitted with an aesthetic sleeve.
Security Rating	BSI PAS 68: 2010 V/7500/64/90:4.0/16.7 <i>Minimum tested array – 3 bollard foundation</i>
Operation Type	Fixed Security Bollard



ATG

ATA

SP40 HIGH-SECURITY FIXED BOLLARD

Product Overview

The ATG Access SP40 High-Security Fixed Bollard is a high-performance bollard, offering a galvanised finish as standard. Alternatively, the bollard can be coated to any RAL colour specified or fitted with a decorative sleeve.

This product provides a cost-effective solution for perimeter security requirements and meets the security rating for most perimeter security projects.

ATG Access has a variety of complementary automatic, lift-out or manually retractable products for additional vehicle access requirements in order to provide a holistic perimeter security offering.

Successfully impact tested to 64 kph with a 7,500 kg vehicle, this product is perfect for both urban and industrial security scenarios.

Only available in a fixed variation, this product must be installed within an approved, reinforced concrete foundation. With a minimum embedment of 500 mm, this product must be installed to comply with the BSI PAS 69 1.2 m spacing requirements.

For sites requiring perimeter protection with limited excavation depth available, ATG Access range of shallow foundation-fixed bollards may be more suitable.