

# WESTMINSTER FIXED BOLLARD



## Technical Specifications

**Bollard Dimensions** 260 mm (front face)  
125 mm (side profile)

**Height Above Ground** 1,065 mm

**Foundation Depth** 800 mm

**Finishes Available** Black primed Manganese steel. Can be fitted with logo or crest.

**Security Rating** **BSI PAS 68:** 2013 v/7500[N3]/64/90:0.0/5.3  
*Minimum tested array – 3 units*

**Operation Type** Fixed Security Bollard



## WESTMINSTER FIXED BOLLARD

### Product Overview

The Westminster Fixed Bollard is manufactured from micro-engineered steel which has a high impact 'toughness' and the ability to absorb massive amounts of energy without fracturing. This material is incredibly strong and corrosion resistant.

This heritage-style bollard is available in a lift-out, shallow-foundation or traditional-depth fixed model.

With a ribbed profile and peaked top, within the front fascia there is a specifically-designed section to enable a corporate logo or crest to be inserted. The product can be supplied unpainted or with a primed finish. Typically finished in black paint.

Installed within a foundation depth of 750 mm, the Westminster fixed bollard is ideal for applications where foundation depth is not an issue and where no restrictions apply.

The foundation for this product is a concrete and rebar structure with 1.2 spacings needing to be adhered to to comply with BSI PAS 69.

You will find the City of Westminster crest displayed on most of the bollards installed within the Westminster area. These incredibly strong products have been installed as far afield as Melbourne Australia!